



液压切纸机 (重型)

Heavy-duty Hydraulic Paper Cutter

成冠 5310FT/5610FT/6810FT
Chengguan 5310FT/5610FT/6810FT



● 高密度加长多回路红外保护
High-density extended multi-zone infrared protection
有效的保证设备及人身的安全
Provides effective protection for both equipment and personnel safety.




● 整体铸件龙门设计
Integrated Cast Gantry Design
机器更加稳定，经久耐用，耐磨不变形，持久保持机器精度
More stable, durable, wear-resistant, and deformation-resistant, ensuring long-lasting machine precision.



● 推纸器采用混合伺服定位
The paper pusher adopts hybrid servo positioning
定位精度保持 0.02mm
maintaining a positioning accuracy of 0.02mm



● 进口单项阀板式液压控制
Imported Single-Stage Valve Plate Hydraulic Control
保持压力均衡，加快下刀速度，增大压力力度，保持切纸深浅一致，减少刀片及刀条损耗
Maintains pressure balance, increases cutting speed and pressure, ensures consistent cutting depth, and reduces blade and strip wear.



● 加厚刀架、加大刀片
Reinforced Knife Rest & Enlarged Blades
保持切刀的力度及精度，提高刀片的耐用度
Maintains cutting force and precision, enhancing blade durability.



● 高精度电子手轮微调
High-precision electronic handwheel for fine adjustment
保证裁切尺寸精度
Ensures cutting size accuracy




● 12mm 加厚平台
12mm thickened worktable
不变形，不磨损，保证机器精度
No deformation or wear, ensuring machine precision



● 大功率静音液压系统
High-power silent hydraulic system
2.5 千瓦大功率电机，确保机器裁切厚度及精度，减小机器的磨损和噪音
2.5 kW high-power main motor, ensuring cutting thickness and precision, reducing machine wear and noise.



● 10 寸彩色触屏智能控制
10-inch color touchscreen with smart control
三种裁切模式，加减自动计算，裁切尺寸误差补偿，操作简单，易学易懂
Three cutting modes, automatic calculation of adjustments, cutting size error compensation, simple operation, easy to learn and use.



● 双导轨、进口滚珠式丝杠
Dual guide rails, imported ball-screw system
避免推纸器的歪斜，减少推纸噪音，确保切纸精度
Prevents paper pusher skewing, reduces pushing noise, and ensures cutting accuracy.

型号 Model	5310FT	5610FT	6810FT
参数 Specifications			
最大裁切门幅 Max cutting width :	530MM	560MM	680MM
最大裁切长度 Max cutting length :	530MM	560MM	680MM
最小裁切门幅 Min Cutting Width :		30MM	
最大裁切高度 Max Cutting Height :		100MM	
最小压纸压力 Min Pressing Force :		100KG	
最大压纸压力 Max Pressing Force :	1200KG	1300KG	1500KG
裁切速度 Cutting Speed :	25 次/分钟 (25cuts/min)		
压力系统 Pressure System :	双液压静音，进口单油路液压片控制 (Dual Hydraulic Silent Imported Single-Line Hydraulic Plate Control)		
导轨 Guide Rails :	双导轨+滚珠式螺纹 (Dual Guide Rails + Needle Roller Thread)		
重量 Weight :	520KG	550KG	580KG
机器尺寸 Machine Dimensions :	1250*950*1450MM	1300*1000*1450MM	1450*1100*1500MM